

# C2R

## RECIRCULATING CONE CRUSHER

The McCloskey™ C2R recirculating cone crusher combines the productivity of the 38" cone with the versatility of a full screening and recirculating system, allowing operators to produce a high quality crushed and screened final product with one machine.

The C2R distinguishes itself as an entry-level cone with full level features like an anti-spin system, load and material level monitoring, fully hydraulic push button CSS adjust and full hydraulic relief system. The 5x10 High Energy Screenbox allows greater control over the final product.



### RECIRCULATING SYSTEM

Recirculation conveyor allows operators to produce a crushed and screened final product with one machine.



### RECIRCULATION SCREEN

5 X 10 High Energy Screenbox has a user-friendly wedge system for faster screen change

### MAGNET

Reversible magnet enables material separation from the source material.



### FEEDER

Steel hopper with adjustable feed rate via control panel, remote control or fully automatic regulation with feedback from the cone

Engine	350 Hp (261 kW) - 360 Hp (268 kW)
Cone	MC200
Feed Opening	38" (914mm)
Feeder Belt Width	42" (1050mm)
Hopper Volume	6.2m <sup>3</sup> (8.1yd <sup>3</sup> )
Crusher Drive	Direct Drive
CSS Adjustment	Hydraulic
Transport Height	11' - 2" (3.4m)
Transport Length	60' - 9" (18.52m)
Transport Width	11' - 5" (3.49m)
Weight	114,640 lb (52,000kg) (est.)
Stockpile Height - Main Conveyor	13' - 10.8" (4281mm)
Main Conveyor Belt Width	48" (1200mm)