CANTER 516

DUONIC AMT





4,983kg



Power/Torque: 110kW/370Nm



Wheelbase: 3,400mm (E)

- Electronic Brake System NEW
- Electronic Stability Control NEW
- Active Emergency Braking System NEW 30,000km service intervals
- Lane Departure Warning System NEW
- 5yr/200,000km warranty NEW



SPECIFICATIONS - CANTER 516 CITY CREW CAB

MODEL

4x2 516

CITY CREW CAB

6 SP.

AMT

FEA21ER3WFBC

WHEELBASE (mm)

3,400 (E)

GVM (kg)


GCM (kg)

4,983

8,483

ENGINE	
Engine Version	FUSO 4P10-T4 Euro 5 Diesel
Configuration	4 Cyl. In-line DOHC, 4-Valve
Туре	Variable Geometry Turbo Charged Air to Air Intercooled
Displacement	3 litre (2998cc)
Power (DIN)	110kW @ 2840~3500rpm
Torque (DIN)	370Nm @ 1350~2840rpm
Maximum Engine Speed	4100rpm
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled with Viscous fan, 14.1L capacity. Engine oil cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH)
Emission Control	Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9
Emission Level	EURO 5 (ADR 80/03) and EEV rated (Enhanced Environmentally-Friendly Vehicle)

4	P1	n.	5	4



FUEL	
Injection System	Bosch Common Rail Direct Injection
	Bosch Piezo Technology Injectors
Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity (L)	100
Filtration	Filter with Water Separator and Indicator Sensor

ELECTRICAL	
Voltage	12V Negative Earth
Alternator Capacity	12V-110 amp
Battery Specification	Heavy Duty 115D31L
Headlamp Type (W)	Halogen 2 x 55/60
Fog lamp in bumper	Standard

CLUTCH	
Clutch Model	DUONIC Automated Manual (no clutch pedal)
Туре	Dual Clutch (Wet Multi-plate)

TRANSMISS	SION
Version	FUSO DUONIC M038S6
Type / Speeds	6 Speed Automated Manual with Auto and Manual Modes
Features	Virtually Instant Gear Changes In-Dash Gear Lever with Park Brake Position ECO Mode to Minimise Fuel Usage
Ratios	1st: 5.397 5th: 1.000 2nd: 3.788 6th: 0.701 3rd: 2.310 Rev. 5.397 4th: 1.474
PTO Opening	LH Side

FRONT AXLE	
Axle	FUSO F200T Independent Front Suspension Type
Design Capacity (kg)	2,300
Max Operating Capacity (kg)	2,300

Туре	Double Wishbone Independent Front Suspension with Coil Springs and Shock Absorbers

REAR AXLE	
Axle	FUSO D03 Full Floating Banjo Type
Ratio	4.444:1
Design Capacity (kg)	3,800
Max Operating Capacity (kg)	3,800

REAR SUSPENSION	
Туре	Steel Suspension
Details	Taper Leaf Spring with Stabiliser Bar and Double Acting Shock Absorbers
Size Main Leaves (mm)	1100 x 70

STEERING	
Power Assisted	Tilt/Telescopic Adjustable Steering Wheel
BRAKES	
Туре	Hydraulic Dual Circuit with Front and Rear Single Caliper Discs
Size Front / Rear (mm)	276 x 28
Features	ABS + EBD + EBS Exhaust Brake Brake Priority System
Park Brake	Transmission Mounted

SPECS - CANTER 516 CITY CREW CAB

WHEELS AND TYRES

Wheel Size	15.0 x 5.0K-115	
Tyre Size All	195 / 85R15	
Spare Tyre Carrier	Yes	

CHASSIS

Size (mm) 188 x 60 x 4

Refer to the bodybuilders guidelines on the Fuso website (www.fuso.co.nz) before mounting a body or modifying the chassis

INSTRUMENTS

Gauges	Speedometer with Odometer Tachometer; Fuel Level; Water Temperature	
Colour Information Display	Fuel Consumption	

DPF Bar Chart from 1~9 Water Temperature

Maintenance Reminder System

Tripmeters

STANDARD FEATURES

Cab Cooling and Heating	Air Conditioner / Heater / Demister
Accessory Power	12V Accessory Power Outlet / Cigar Lighter
Driving	Keyless Central Locking Electric Windows (front only)
Storage	Dual Overhead Storage Pockets In-Dash Centre Document Storage Door Storage Pockets Storage Under Rear Crew Seats

CAB FEATURES

CADILATOR	
Туре	All Steel Forward Control Fixed Cab
Mounting	6 Point Isolated Rubber
Colour	Natural White (W31)
Interior	Fully Trimmed cab with vinyl floor covering
Seating Capacity	6
Seat (driver)	Heavy Duty with LH Arm Rest Adjustable Lumbar Support
Seats (front passengers)	Flat Folding, 2 Passenger Bench
Seats (crew cab rear)	Low Back Bench Seat

SERVICE INTERVALS

30,000km / 12 months

Vehicles operating in harsh environments may be subject to reduced service intervals.

WARRANTY

5 years / 200,000km

Simply have your vehicle serviced at an authorised FUSO Service Centre, at the recommended servicing intervals, and you are covered by an additional $2\ \text{year}/100,\!000 \text{km}$ FUSO warranty on top of the first $3\ \text{years}/100,\!000 \text{km}.$ That's a total of 5 years / 200,000km cover.

Refer to terms and conditions in the FUSO warranty booklet for full details.

SAFETY FEATURES

ACTIVE SAFETY FEATURES

Electronic Brake System (EBS)	Yes	NEW
Electronic Stability Control (ESC)	Yes	NEW
Active Emergency Braking System (AEBS)	Yes	NEW
Lane Departure Warning System (LDWS)	Yes	NEW

2019 MODEL

SAFETY

CAB	
Structure	Front Door Side Impact Beams
Airbags	Driver's (steering wheel) Passenger's (dashboard) NEW
Seatbelts	ELR 3-Point (+ height-adjustable with pre tensioner for driver) Lap Belt (centre passenger)
Driver's Seat	Spring-suspended
Steering Wheel	Energy-absorbing Adjustable (height and reach)
Rearview Mirrors	Heated
Fog Lamps	Yes
Keyless Central Locking	Yes
7" Touchscreen Media Unit	AM/FM/DAB + USB + AUX NEW Apple CarPlay and Android Auto Wi-Fi enabled for Internet Radio Bluetooth

32GB capacity storage HD Reverse Camera included †

СПАЗЗІЗ	
Speed Limter	Yes (activated and adjustable by FUSO dealer)
Anti-Lock Braking System (ABS)	Yes
Anti-Slip Regulator (ASR)	Yes
Electronic Brake Force Distribution (EBD)	Yes
Disc Brakes	Auto-Adjusting, 4 Wheel Single Caliper
Brake Priority System	Yes
Exhaust Brake	Yes
Hill Start Assist	Yes
Reverse Warning Buzzer	Yes
Anti Roll Bar	Yes
Brake Wear Indicator	Yes

OPTIONS

† Additional Multimedia Display Cameras (up to 4)

Truck Specific GPS Navigation

Reversing Sensors

Tyre Pressure Monitoring System

Wireless Phone Charge Pocket

KERB WEIGHTS AND MAX AXLE LOADS (kg)

		Vehicle Ratings**		Max Axle Loadings**		Kerb Weights*		
Model		GVM	GCM	Front	Rear	Front	Rear	Total
4x2 516 City Crew Cab 6 Sp. AMT	FEA21ER3WFBC	4,983	8,483	2,300	3,800	1,515	665	2,180


^{*} Weights (est.) includes 10L fuel and spare wheel and are subject to 2.5% variation (+/-)

^{**} Vehicle ratings and max axle loadings may be limited by local regulations.

SPECIFICATIONS - CANTER 516 CITY CREW CAB

PERF	ORMANCE	
Turning Circ metres)	le (kerb to kerb -	9.8
Road Speed Engine Spee	(km/h) at Max d	144
Engine Spee (top gear)	d (rpm) at 90km/hr	2150
Gradeability (theoretical)	at Rated GVM *	41%
Notes	*This is theoretica vary under differe	al performance only. Actual performance may ent conditions

DIMENSIONS (mm)	
Wheelbase	3,400
Length Overall	5,785
Height Overall	1,995
Width Overall	1,865
Width Rear Axle	1,865
Width Front Track	1,390
Width Rear Track	1,435
Width Frame	700
Height Frame at Rear Axle	729



CANTER 516 CITY CREW CAB - 'E' WHEELBASE



Scale = 1:50 (20mm = 1 metre). This scale is accurate when used on the original spec sheet, be aware that enlarging these illustrations can alter the scale and cause incorrect measurements. Fuso New Zealand and its authorised dealers always recommend customers seek professional advice from independent sources before commencing any engineering activities.

A policy of continual improvement means that specifications detailed in this brochure are subject to change without notice. Contact your authorised Fuso dealer to confirm current specifications. Fuso is a registered trademark of Mitsubishi Fuso Truck & Bus Corporation. Copyright © Fuso NZ (2017)

