EXTRA LONG WHEELBASE

CANTER 918

DUONIC AMT OR MANUAL





GVM: 8,550kg



Power/Torque: 129kW/430Nm



- Electronic Brake System NEW
- **Electronic Stability Control NEW**
- Active Emergency Braking System NEW 30,000km service intervals
- Lane Departure Warning System NEW
- 5yr/200,000km warranty NEW




SPECIFICATIONS - CANTER 918 XLWB

MODEL	WHEELBASE (mm)	GVM (kg)	GCM (kg)
-------	----------------	----------	----------

4x2 918	WIDE CAB	6 SP.	AMT	FECX1KR3SFBD	4,750 (K)	8,550	12,050
4x2 918	WIDE CAB	5 SP.	MAN	FECX1KR4SFBD	4,750 (K)	8,550	12,050

Engine Varsion	FUSO 4P10-T6 EURO 5 Diesel
Engine Version	
Configuration	4 Cyl. In-line DOHC, 4-Valve
Туре	Variable Geometry Turbo Charged Air to Air Intercooled
Displacement	3 litre (2998cc)
Power (DIN)	129kW @ 2860~3500грm
Torque (DIN)	430Nm @ 1600~2860rpm
Maximum Engine Speed (rpm)	4100
Compression Ratio	17.5:1
Cooling System / Oil Cooler	Water cooled with Viscous fan, 14.1L capacity. Engine oil cooler
Air Cleaner	Paper Element Type with Restrictor Indicator. Vertical Intake Mounted on Clean Air Side (RH)
Cold Start Preheat	Standard
Emission Control	Diesel Particulate Filter (DPF) Exhaust Dash Display DPF Status 0~9 (Empty~Full) Parked Regeneration possible from 7~9 Selective Catalytic Reduction (SCR) after- treatment system (BlueTec)
Emission Level	EURO 5 (ADR 80/03) and EEV rated (Enhanced Environmentally-Friendly Vehicle)

4P10-T6



FUEL	
Injection System	Bosch Common Rail Direct Injection Bosch Piezo Technology Injectors
Tank Type	Rectangular Steel Tank with Locking Cap
Fuel Capacity (L)	100
Filtration	Filter with Water Separator and Indicator Sensor
AdBlue Exhaust Fluid Capacity (L)	12

ELECTRICAL	
Voltage	12V Negative Earth
Alternator Capacity	12V-110 amp
Battery Specification	Heavy Duty 115D31L x 2
Headlamp Type	Halogen 2x55W/60W
Fog lamp in bumper	Standard

CLUTCH		
	DUONIC AMT	Manual
Clutch Model	DUONIC Automated Manual (no clutch pedal)	FUSO C4W30
Туре	Dual Clutch (Wet Multi-plate)	Single Dry Plate, Direct Hydraulic Type, 300mm

TRANSMISSION		
	DUONIC AMT	Manual
Version	FUSO DUONIC M038S6	FUSO M038S5
Type / Speeds	6 Speed Automated Manual with Auto and Manual Modes	5 Speed with In-Dash Gearshift Lever
Features	Virtually Instant Gear Changes In-Dash Gear Lever with Park Brake Position ECO Mode to Minimise Fuel Usage	Synchromesh 2nd-5th
Ratios	1st: 5.397 2nd: 3.788 3rd: 2.310 4th: 1.474 5th: 1.000 6th: 0.701 Rev. 5.397	1st: 5.494 2nd: 3.193 3rd: 1.689 4th: 1.000 5th: 0.723 Rev. 4.494
PTO Opening	LH Side	LH Side

FRONT AXLE	
Axle Version	FUSO F350T "I" Beam
Design Capacity (kg)	3,100
Max Operating Capacity (kg)	3,100

FRONT SUSPENSION Type Multi Leaf Spring with Stabiliser Bar and Double Acting Shock Absorbers Size (mm) 1,150 x 70

REAR AXLE		
Axle	FUSO D035 Full Flo	oating Banjo
Ratio	DUONIC 6.166:1	Manual 5.285:1
Design Capacity (kg)	6,000	
Max Operating Capacity (kg)	6,000	

REAR SUSPENSION	
Туре	Steel Suspension
Details	Multi Leaf Spring with Stabiliser Bar and Double Acting Shock Absorbers
Size Main Leaves (mm)	1,250 x 70
Size Helper Leaves (mm)	880 x 70
STEEDING	

Power Assisted	Tilt / Telescopic Adjustable Steering Wheel

SPECIFICATIONS - CANTER 918 XLWB

BRAKES Туре Hydraulic Dual Circuit with Front and Rear Twin Caliper Disc Brakes Size Front / Rear (mm) ABS + EBD + EBS **Features** Exhaust Brake Brake Priority System Park Brake Transmission Mounted

WHEELS AND TYRES	
Wheel Size	17.5 x 6.0-127
Tyre Size All	215 / 75R17.5
Spare Tyre Carrier	Yes

7		
CHASSIS		
Size (mm)	212 x 65 x 6	

Refer to the bodybuilders guidelines on the Fuso website (www.fuso.co.nz) before mounting a body or modifying the chassis

INSTRUMENTS	
Gauges	Speedometer with Odometer, Tachometer Fuel Level, Water Temperature, AdBlue Level
Colour Information Display	Fuel Consumption, DPF Bar Chart from 1~9; Water Temperature, Maintenance Reminder System, Date and Time, Tripmeters x 2

STANDARD F	EATURES
Cab Cooling & Heating	Air Conditioner / Heater / Demister
Accessory Power	12V Accessory Power Outlet / Cigar Lighter
Driving	Keyless Central Locking Electric Windows
Storage	Dual Overhead Storage Pockets, In-Dash Centre Document Storage Door Storage Pockets, Lockable Glove Box

CAB FEATUR	RES
Туре	All Steel Forward Control Fixed Cab
Mounting	Hydroelastic 4 Point
Colour	Natural White (W31)
Interior	Fully Trimmed Cab with Vinyl Floor Covering
Seating Capacity	3
Seat (driver)	Heavy Duty Suspended with LH Arm Rest Adjustable Lumbar Support and Weight Adjustment
Seats (passenger)	Flat Folding, 2 Passenger Bench

SERVICE INTERVALS

30,000km / 12 months

Vehicles operating in harsh environments may be subject to reduced service

WARRANTY

5 years / 200,000km Simply have your vehicle serviced at an authorised FUSO Service Centre, NEW at the recommended servicing intervals, and you are covered by an additional $2\ \text{year}/100,\!000 \text{km}$ FUSO warranty on top of the first $3\ \text{years}/100,\!000 \text{km}.$ That's a total of 5 years / 200,000km cover.

Refer to terms and conditions in the FUSO warranty booklet for full details.

SAFETY FEATURES

ACTIVE SAFETY FEATURES		STOTEMS
Electronic Brake System (EBS)	Yes	NEW
Electronic Stability Control (ESC)	Yes	NEW
Active Emergency Braking System (AEBS)	Yes	NEW
Lane Departure Warning System (LDWS)	Yes	NEW

Lane Departure Warning System (LDWS)	Yes	W
CAB		
Structure	ECE R-29 Reinforced Cab Side Intrusion Bar	
Airbags	Driver's (steering wheel) Passenger's (dashboard)	W
Seatbelts	ELR 3-Point (+ height-adjustable with pre tensioner for driver) Lap Belt (centre passenger)	
Driver's Seat	Spring-suspended	
Steering Wheel	Energy-absorbing Adjustable (height and reach)	
Rearview Mirrors	Heated	
Fog Lamps	Yes	
Keyless Central Locking	Yes	
7" Touchscreen Media Unit	AM/FM/DAB + USB + AUX NE Apple CarPlay and Android Auto Wi-Fi enabled for Internet Radio Bluetooth 32GB capacity storage HD Reverse Camera included †	W

CHASSIS	
Speed Limter	Yes (activated and adjustable by FUSO dealer)
Anti-Lock Braking System (ABS)	Yes
Anti-Slip Regulator (ASR)	Yes
Electronic Brake Force Distribution (EBD)	Yes
Disc Brakes	Auto-Adjusting, 4 Wheel Dual Caliper
Brake Priority System	Yes
Exhaust Brake	Yes
Hill Start Assist	Yes (adjustable engagement on manual transmission)
Reverse Warning Buzzer	Yes
Anti Roll Bar	Yes
Brake Wear Indicator	Yes
	············

OPTIONS

+		,	۸	١	c	ł	•	ł	i	1	Ė	i	c)	r	1	a	ا		I	٧	٨		u	I	t	ci	i	n	r	1	e	•	c	ł	i	ä	1))	i	S	ŀ	þ	ı	ä	3	y	,	(C	a	r	۲	1	e	r	č	3	s	((u	ı	0		t	c)	4	4	.))		
	• • •	• • •		• •	• •	• •	٠	•	• •	•		• •	• •	•	٠			•	•	•••	•		•	•	•	•	••	• •	•			• •	•		• •	• •	• •		•	• •	٠	•	• •	•						•	• •	• •	• •		•••	• •	• • •	•	•••	• • •	• • •	•••	•		•	•	• •	• •		•••	• •	•	•	• • •	•••	•••	•

Truck Specific GPS Navigation

Reversing Sensors

Tyre Pressure Monitoring System

Wireless Phone Charge Pocket

Campervan spec - Underseat Engine Access

KERB WEIGHTS AND	MAX AXLE LOA	DS (kg)						
		Vehicle	Ratings**	Max Axle	Loadings**		Kerb Weights	*
Model		GVM	GCM	Front	Rear	Front	Rear	Total
4x2 918 Wide Cab 6 Sp. AMT	FECX1KR3SFBD	8,550	12,050	3,100	6,000	1,635	890	2,525
4x2 918 Wide Cab 5 Sp. MAN	FECX1KR4SFBD	8,550	12,050	3,100	6,000	1,620	890	2,510


^{*} Weights (est.) includes 10L fuel and spare wheel and are subject to 2.5% variation (+/-)

^{**} Vehicle ratings and max axle loadings may be limited by local regulations.

SPECIFICATIONS - CANTER 918 XLWB

PERFORMA	NCE		
		DUONIC AMT	Manual
Turning Circle (kerb to k	cerb -	16.6	16.6
Road Speed (km/h) at <i>N</i> Speed	Nax Engine	130	130
Engine Speed (rpm) at 9 (top gear)	00km/hr	2420	2740
Gradeability at Rated G' (theoretical)*	VM	32%	27%
		Il performance only.	Actual performance may

DIMENSIONS (mm)	
	K Wheelbase
Wheelbase	4,750
Length Overall	7,735
Height Overall	2,185
Width Overall	2,140
Width Rear Axle	2,140
Width Front Track	1,675
Width Rear Track	1,670
Width Frame	850
Height Frame at Rear Axle	795



Scale = 1:50 (20mm = 1 metre). This scale is accurate when used on the original spec sheet, be aware that enlarging these illustrations can alter the scale and cause incorrect measurements. Fuso New Zealand and its authorised dealers always recommend customers seek professional advice from independent sources before commencing any engineering activities.

A policy of continual improvement means that specifications detailed in this brochure are subject to change without notice. Contact your authorised Fuso dealer to confirm current specifications. Fuso is a registered trademark of Mitsubishi Fuso Truck & Bus Corporation. Copyright © Fuso NZ (2017)

