



# MB-R800

**MB**  
THE CRUSHING EVOLUTION



## ACCESSORIES

- RECOMMENDED SPARE PARTS KIT
- FIXED COUPLING
- LOW SET DRUM KIT
- FULL SET DRUM KIT
- DUST SUPPRESSION KIT
- HIGH OIL TEMPERATURE REDUCING DEVICE
- ROCK AND ASPHALT PICK KITS
- 24 MONTHS WARRANTY



## SPECIFICATIONS

EQUIPMENT	 $\geq 10 \leq 22$ Ton
RECOMMENDED OIL FLOW (MIN)	200-300 l/min.
INLET MAXIMUM PRESSURE	> 350 bar
DRAIN-OUT MAXIMUM PRESSURE	< 4 bar
OUTPUT TORQUE	10000 Nm
PICK FORCE	33900 N
WEIGHT	1 Ton
SPEED/MIN.	60/80 min/max

## AREAS OF APPLICATION



TUNNELS



UTILITY  
WORK



URBAN  
JOB SITES



ROAD WORKS



PROFILING  
OF ROCKS AND  
CONCRETE WALLS



DEMOLITION



EXCAVATION  
AND CREATION  
OF FOUNDATIONS



AGRICULTURAL  
AND FOREST  
AREAS

The data provided above is not binding, as the manufacturer reserves itself the right to make improvements to its products at any time and with no advance notice. References to excavator weights are approximate and many may be subject to changes.

Rev. 2019 / 03

in f t You Tube you

WWW.MBCRUSHER.COM