

S130

HIGH ENERGY SCREENER


The McCloskey S130 High Energy Screener is used across a wide range of applications, including aggregate, coal, crusher circuits and wood chips. The S130 is renowned for its fine sand screening and is impressing customers worldwide with its production capacities.

With the S130, you get class-leading S-Range features like the aggressive High Energy Screenbox and user-friendly operation. The S130's unique size is designed to meet demands of operators who require significantly more screening capacity than a 10' or 11' screenbox, but may not require the higher capacity of a 20' plant.



SCREENBOX



High Energy 14x5 (4200x1524mm) screenbox provides comparable product capacity with other larger class competitor's models.



HOPPER
14ft (4267mm) grid opening allows the use of larger loading shovels.

48" MAIN CONVEYOR

48" (1200mm) feed conveyor enables high capacity screening.



WEDGE SYSTEM
User friendly wedge system ensures faster screen changes.

LINKAGE SYSTEM

Hydraulic Screenbox linkage system, allows greater accessibility for screen change and enables optimum screen coverage at varying screenbox angles.



Engine	100 hp (75 kw) Diesel
Transport Height	11' 2" (3.40m) (Tracked)
Transport Length	54' 2" (16.52m) 15' Hopper 54' 2" (15.61m) 12' Hopper
Transport Width	9' 6" (2.90m)
Weight - Tracked Model	59,965 lbs (27,200kg)
Stockpile Height - Tail Conveyor	12' 8" (3.87m)
Stockpile Height - Side Conveyor	15' 1" (4.60m)
Screenbox Dimensions	5'x14' (1.52m x 4.27m)