

## TF80-WF80

### HIGH EFFICIENCY FEEDER STACKER

The TF80 - WF80 Mobile Feeder Stacker is enhancing the process of stockpiling materials that traditionally can cause blockages in conventional stackers. The TF80 - WF80 facilitates the handling and stockpiling of large wood waste, bark, compost and topsoil, all of which can be fed into the hopper with large loaders and excavators.

In addition to the enhanced mobility, a large feeder hopper, wide heavy duty 80' long conveyor, and a heavy duty feeder make the TF80 - WF80 a robust, mobile stockpiling conveyor for use across a number of industries.

Available with numerous custom options to meet each customer's unique material requirements.



#### HOPPER

Up To 23.0 Cubic Yard (17.0m<sup>3</sup>) Hopper. Includes a 48" Chevron feed belt to evenly convey material such as wood chips and logs without bridging.



**48" CHEVRON MAIN CONVEYOR**  
Allows stockpiling of high volume materials without spillage or bottlenecks.

#### OPEN ACCESS ENGINE BAY

Provides class leading access to hydraulic valves and the transverse mounted Diesel engine.



**TRACK OR WHEEL MOBILITY**  
Fully portable stockpiling solutions available as wheel mounted trailer unit or a track unit for maximum onsite mobility.

#### HYDRAULIC TOP FOLD

Straightforward hydraulic controls to fold and unfold, raise and lower conveyor.



Engine - Power Unit Diesel (Dual Power option)

Transport Height 11' 7" (3.54m)

Transport Length 63' 10" (19.46m)

Transport Width 9' 7" (2.92m)

Weight 62,850 lb (28,500kg)

Stockpile Height 42' 6" (12.94m)

Stockpile Capacity 5,280 cu. yds. (4,037 cu. m)

Production 750 US TPH (680 metric TPH)

Belt 48" x 80' (1220mm x 19.35m)

Stockpiling Angles 0° - 29°