NMR250Tipper



4x2




MODEL	NMR250 Tipper
GVM (kg)	5,995
GCM (kg)	9,500*
Max Power (kW)	110
Wheelbase (mm	2490
License**	Class 1

*AMT transmission models 8,000Kg GCM

ENGINE						
Engine Model	ISUZU 4JJ1-TCS Type 4 cyl 16 valve,					
Displacement	2,999cc Compression Ratio 16.5:1					
Max Power (DIN Nett)	110kW (150 HP) @2,800 RPM					
Max Torque (DIN Nett)	375Nm (276 lb.ft) @ 1,450 rpm					
Emission Control System	Euro V with cooled EGR and Diesel Particulate Diffuser					
Fuel System	Electronically controlled direct injection, high pressure common rail. 75 litre fuel tank with lockable fuel cap. Water-in-fuel sensor standard					
Air Intake System	Electronically controlled variable nozzle turbo charger with air-to-air					





CLUTCH	PERFORMANCE						
Standard:	Auto-adjusting vacuum assisted hydraulic control. Single plate 300mm diameter.	Est Engine RPM @90km/h :2330, (AMT) 2185	Speed Limit:	opt: 90/100kmh			
with AMT:	Automated hydraulically controlled wet clutch & torque convertor with lock up.	Low Speed Gradeability @ GVM (lowest forward ge	49%				

TRANSMISSION		AXLES			
Manual:	ISUZU MYY5T - 5 spd manual, (Standard). Synchromesh on 1st to 5th	Front Isuzu FO26, Fully independent wishbone. 2,600 kg capac			
Ratios (:1)	1st 5.315, 2nd 3.053 3rd 1.655, 4th 1.0, 5th 0.721, Rev 5.701	Rear	Isuzu RO50, Full floating banjo type housing. 5,000 kg capcity		
AMT	ISUZU MYY6E 6-Speed Automated Manual (AMT) full automatic and	Ratio:	5.125 (man) 4.30 (AMT		
(optional)	sequential manual shift modes	WHEELS AND TYRES			
Ratios (:1)	1st 5.979, 2nd 3.434 3rd 1.862, 4th 1.297, 5th 1.000, 6th 0.750, Rev 5.701	16.0 x 5.5J 5-stud steel wheel rims			
		Front axle: 195/85 R16C 114/112 L			
PTO:	Provision on LHS of transmission case, countershaft driven & with wiring harness provided	Rear axle: 195/85 R16C 114/112 L			
		Silver painted wheel rims and frame mounted spare wheel			

CHASSIS			
Suspension	Chassis	Brakes	Electrical & Steering
Front Suspension Coil spring - independent Double acting shock absorber Stabiliser bar Rear Suspension Taper leaf spring with helper spring Double acting shock absorbers	Cold riveted ladder frame Rail dimensions (mm)180x65x4 SAPH440 weldable steel	 Auto adjusting disc brakes, dual circuit hydraulic control, vacuum assistance with electronic brake force distribution (EBD). ABS, ASR traction control, EVSC stability control. Hill Assist - except with AMT. Front & Rear disc diameter: 293 mm. 190 mm diameter drum park brake mounted on rear of transmission. Vacuum controlled exhaust brake. 	Electrical: • 24 volt negative earth system • 90-amp alternator • Batteries - 2 x 80D26L 80Ah, 630CCA. Steering: • Power assisted rack and pinion. • Turns lock to lock: 4.2 • Maximum angle: 38° (inside wheel) / 34.75° (outside wheel)

NMR250Tipper



4x2

Feb20

CAB AND INTERIOR

Cab Exterior

- All steel construction, high tensile steel on cab under-frame and side impact beam reinforcement
- Cab is fully compliant with ECE-R29 crash tests
- Manual cab tilt to 45° with torsion bar assistance
- Liquid filled front and rear cab mounts
- · Heavy duty non-slip cab entry steps
- · 90° opening doors
- · Cab mounted main mirrors on front of cab
- Halogen multi-reflector headlamps with integral front turn signals
- · Additional door mounted turn signals
- · Polycarbonate front bumper with steel frame
- · Combined brake/turn/reverse/marker lamps
- · Registration plate lamps
- · Reverse alarm buzzer standard

Tipper body:

- · All steel body with drop sides. Auto release two-way
- tailgate.
- · Auto release body lockdown hook.
- Shovel rack. LHS and RHS rope rails. Non-slip side steps.
- · 20 second raise / 20 second lower time.
- · Cubic volume: 2.0 m3
- Deck plate thickness: 3.2 mm
 Side / front / tail plate thickness: 2.3 mm

Cab Interior

- Contoured adjustable driver's bucket seat with mechanical suspension rated to 130 kg
- 3-point seatbelts in all outboard seating positions. Driver and outboard front passenger seatbelts fitted with pretensioner. Centre seat lap belt
- Air bag for both outer seats.
- · SRS including air bag for driver and passenger
- Door and pillar entry assist grips both sides
- Lined interior, padded roof lining & vinyl floor covers
- RH and LH overhead storage shelf
- Height/reach adj steering column, soft-feel urethane steering wheel with audio controls
- · Electric windows
- · Central locking with keyless entry & immobiliser
- · Twin cup holders, 24V cigarette lighter
- Integrated air conditioning with 4 speed fan
- Door mounted storage pockets
- Fluorescent interior light
- · Spare DIN sized communications compartment
- Multimedia unit with 6.2" LCD touch screen. Android OS. DAB+ digital radio, integrated Bluetooth with voice recognition. Inbuilt media viewer.
 Internet radio via smartphone. 32GB file storage. USB & auxilliary inputs.
- OPTIONS: (full details from your Isuzu dealer). Telematics. Supports up to five camera inputs, one digital camera, reversing sensors, tyre pressure monitoring.
 - ADAS (Advanced Driver Assistance System). Wireless phone charger for QI enabled phones.


Instruments and Controls

- Key-operated engine start/stop & steering lock.
- Hill Assist slow/fast engagement control & on/off switch except with AMT.
- ASR on/off.
- DPD regeneration.
- With AMT: AMT slow/fast gear engagement control, 1st gear start and normal/economy gear selection modes.
- · With AMT: Gear selection control with sequential shift positions.
- Left side combination stalk: Windscreen wipers, washers and exhaust brake.
- · Right side combination stalk: Turn signals, headlamps.
- Electronically driven speedometer and tachometer. Digital odometer with integrated dual tripmeter. Engine coolant temperature and fuel level gauges.
- Warning lamps: Check engine, oil pressure, ABS, SRS airbag, alternator charge, service brakes, park brake, seatbelt unfastened, low fuel level. With AMT: check AMT.
- Indicator lamps: Hill Assist (except with AMT), warm up system, high beam, ASR, EVSC, exhaust brake, turn signals, cruise control, PTO. With AMT: Econo-mode, 1st gear start.
 With AMT: Gear selection display.
- Multi information display: Shows service interval, instantaneous and average fuel consumption, DPD bar chart, hour meter, voltmeter, time/day/date and includes 40-120km/h adjustable vehicle speed warning.


WEIGHTS (KG)								
Model Codes	Model Codes Models	Ratings*		Loading Limits (at ground)*		Chassis Cab Tare Mass**		
woder codes		GVM	GCM	Front	Rear	Front	Rear	Total
NM0520	NMR250 Tipper	5995	9500	2360	4480	1535	1350	2885
NM0620	NMR250 AMT Tipper	5995	8000	2360	4480	1535	1350	2885

^{*} Vehicle ratings and front and rear mass limits are subject to regulatory requirements – Consult your dealer to select a specific vehicle to suit your requirements

^{**} Chassis cab as supplied from the factory including 10 litres of fuel







WARRANTY

Full vehicle warranty: 36 months or 100,000 kilometres whichever occurs first All warranty is subject to terms and conditions as detailed in the Owner's Manual Service and Warranty Supplement

8.7 m

A policy of continuous improvement means that these specifications are subject to change without notice. Contact a Isuzu dealer or visit Isuzu.co.nz to confirm specifications. Images of vehicles are representative only and may differ from the actual vehicle. * * Always refer to NZTA to confirm & for Licensing changes.