

DESIGNED FOR 1.2 TO 2.2 TONNES CARRIERS

COMPACT AND POWERFUL

LANDSCAPING, DEMOLITION, TRENCHING, CIVIL ENGINEERING, INSIDE AND OUTSIDE: VERSATILE AND EFFICIENT


- Hydraulic accumulator: no more regular nitrogen controls and recharges on jobsites.
- Tie rod free, lighter tool locking system: less weight, more power and reliability.
- Made in France: superior quality steel and manufacturing excellence.
- Standard soundproofing for urban jobsites.
- Easy to install, operate and maintain.

KEY ASSET FOR ALL JOBSITES

76	168
82	181
112	247
1,118	44
1,078	42.4
637	25
289	11.3
166	6.53
190	7.48
34	1.33
	82 112 1,118 1,078 637 289 166 190

OPERATING INFORMATION		
CARRIER WEIGHT RANGE (MIN-MAX, MT)		1.2-2.2
OIL FLOW (MIN-MAX, L/MIN / GPM)	17-35	4.5-9.2
MAXIMUM OPERATING PRESSURE (BAR/PSI)	120	1,740
MAXIMUM BACK PRESSURE (BAR/PSI)	32	464
INPUT POWER (KW)		7
STRIKING FREQUENCY (MIN-MAX, BPM)		825-1,700
NOISE LEVEL /10M (DBA)		89
SOUNDPROOFING		standard


OPTIONS	CPN
HOSES PROTECTION KIT	86636701
ADAPTER PLATE	upon request
SPECIAL PAINTING	upon request



CONSUMABLES	CPN
GREASE CARTRIDGES (X48)	86799152

MAINTENANCE KITS	CPN
LEVEL 1	86638954
LEVEL 2	86684594
LEVEL 3	86684602

TOOLS			
DIAMÈTRE (MM)	47/1.85	47/1.85	
LONGUEUR (MM)	475/18.7	475/18.7	
POIDS (KG)	6/13	6/13	
CPN	86621216	86620739	



The content of this brochure constitutes non-binding information and may be changed at any time without notice. Montabert gives, and thebrochure contains, no warranties whatsoever, express or implied. All the contents, including but not limited to text, images, graphics are all subject to copyright and all intellectual property protection. Their use or misuse is strictly prohibited. Montabert, KMC or Komatsu trademarks used herein are the property of their respective compagnies. Nothing contained on this document shall be construed as constituting any commitment by Montabert or as granting any license or right to use any intellectual property.



EN/A4 - SC12.EN.A4.03202