

**ZAXIS-7 series**

**HITACHI**

**Reliable solutions**

**ZAXIS130**



## **HYDRAULIC EXCAVATOR**

Model code : ZX130-7

Engine rated power : 74 kW (ISO14396) /  
73 kW (ISO 9249)

Operating weight : 13 500 - 15 300 kg

Bucket ISO heaped : 0.52 to 0.66m<sup>3</sup>

Model code : ZX130LCN-7

Engine rated power : 74 kW (ISO14396) /  
73 kW (ISO 9249)

Operating weight : 14 100 - 14 700 kg

Bucket ISO heaped : 0.52 to 0.66m<sup>3</sup>



# YOU'RE IN CONTROL

You're at the heart of Hitachi's design for its latest range of excavators. To continuously improve on previous generation machines we've focused on enhancing your experience in the cab as an operator.

We've considered the challenges you face as the owner of a successful business. And we've zoomed in on the ways in which we can support you over the life cycle of your machine.

By putting you at the heart of the Zaxis-7 range, we invite you to take control – over your workspace and your fleet. And by working in partnership, we will help you to create your vision.






## INSIDE



**4. Complete Control**  
In control of your assets




**6. Increase your safety**  
Be in control of your environment




**8. Boost your uptime**  
Improve your profit



**11. Control Zone**  
Feel the difference



**12. Get More from your machine**  
In control of your performance



**13. Specifications**  
Know your machine



# COMPLETE CONTROL

The new Zaxis-7 range of medium excavators puts you firmly in control, so you can feel assured of your machine's performance and supported by the technological expertise and services that Hitachi provides.



The expanded cab interior provides a more comfortable working environment.



Integrated console and seat suspension gives a greater sense of control, and helps to reduce fatigue.



Visibility of the job site is excellent thanks to the Aerial Angle® camera system and new LCD monitor.



Sensors monitor oil continuously and contribute to preventative maintenance, helping to reduce downtime.



ConSite Pocket app allows you to manage and monitor your fleet remotely.



Options such as Hitachi ground engaging tools enable you to enhance the performance of your excavator.



Improved access to components ensures maintenance is quick and easy.



The new HIOS-V hydraulic system reduces fuel consumption and increases efficiency.



The ECO gauge on the monitor indicates how to lower fuel consumption and reduce costs.





# INCREASE YOUR SAFETY

Your ability to work safely is vital, not only for your own wellbeing, but also for the successful completion of any project. To protect yourself and your machine from potential hazards, the new Hitachi Zaxis-7 excavators give you a superior view of your surroundings, so you can see the job site from all angles.

The visibility you enjoy from the cab includes an exceptional 270-degree bird's-eye view with the Aerial Angle® camera system. You can choose from six image options to view the machine's immediate environment, which enables you to control your own safety – as well as that of those around you.

To help you to work more confidently and efficiently, even in the most challenging of conditions, Zaxis-7 excavators are fitted with some impressive new features. From the LED work lights and the windscreen wiper with an increased sweeping area, to the large reflective strips on the counterweight and roller sunshades, you'll have the visibility you need when it matters most.

Attention to detail is also fundamental to a safe working environment – and the repositioning of the pilot shutoff lever is a perfect example. It is now within easy reach to prevent any unintentional actions.






The pilot shutoff lever offers enhanced safety in the cab.



Choose between different image layouts to suit your working environment.



LED work lights improve visibility in challenging conditions.


# BOOST YOUR UPTIME

Completing a project on time and on budget depends on the ability of your construction equipment to perform all day, every day. That's why Hitachi owners have profited from generations of ultra-reliable and durable machinery – and the Zaxis-7 range is no exception.

The latest Hitachi medium excavators have been built to last, so that you can remain in complete control of your assets. They have been tested rigorously and continuously at dedicated facilities in Japan with the goal of significantly boosting your uptime.

As a result, a wide range of durable new components have been fitted to the latest Stage-V compliant machines – even down to the detail of the rigidity of the door hinges. Now standard on our Zaxis-7 range are hydraulic and engine oil monitoring sensors that help to reduce downtime and running costs.


Downtime is prevented by the durable after-treatment system, and also minimised by the priority given to easy maintenance and cleaning – saving you time and money. Peace of mind comes from such features as the two-way disconnect switch. This makes it possible to shut down power without resetting data on the monitor and prevents the battery from discharging during welding.



Durable after-treatment system prevents downtime.



Filters and separator are conveniently located for ease of inspection and replacement.



The air conditioner condenser can be opened for easy cleaning of the condenser and radiator located behind it.



Improvements to the undercarriage have enhanced durability.





Designed for durability and easy maintenance, Zaxis-7 excavators increase uptime and reduce the total cost of ownership.





1

2

3

4

5

16

15

13

14

6

7

8

9

11

12

10



# CONTROL ZONE

Enhanced comfort and safety features are at your fingertips in the refined cab of Zaxis-7 excavators, giving you the power to perform productively, with ease and reduced fatigue.

- 1 **Increased sweeping area of wide view wiper** enhances visibility in difficult working conditions.  
\*(Option only)
- 2 **Air conditioning and audio** are easily controlled via the monitor.
- 3 **Low-reflective colour 8" LCD monitor** is easy to view and navigate.
- 4 **USB power supply and smartphone holder** helps you stay connected.
- 5 **Drinks holder** is easy to detach for cleaning.
- 6 **Additional joystick controls** for effortless operation.
- 7 **Ergonomic design** gives you convenient access to controls.
- 8 **Bluetooth®** for hands-free calls and **DAB+** radio for music while you work.
- 9 **Multifunctional control panel** makes operation easier.
- 10 **Improved sound isolation** makes this one of the quietest cabs in the market.
- 11 **User-friendly storage space** keeps your workspace tidy and clutter-free.
- 12 **12v and 24v outlets** for your electrical devices.
- 13 **One-touch adjustment lever for console** so you can work comfortably in the optimum position.
- 14 **Integrated console and seat suspension** gives a greater sense of control and helps to reduce fatigue.
- 15 **Increased legroom** creates a more spacious cab.
- 16 **Optimal pedal layout** helps to reduce fatigue.



Operation is easy with ergonomically designed controls and switches.



Bluetooth® connection for hands-free calls while you work.

# GET MORE FROM YOUR MACHINE

Designed to work in perfect harmony with your machine, Hitachi preferred durable hydraulic breakers, hydraulic hitches, buckets and Ground Engaging Tools (GET) will increase your profit by maximising productivity and uptime. Manufactured to the same high standards as all Hitachi construction equipment, they offer unrivalled reliability and exceptional performance.

## Buckets

You can increase the versatility of your excavator by choosing the right bucket for the job. For loading light materials or heavy-duty work, Hitachi buckets can be customised to meet your needs. You have a wide range of options to choose from Hitachi supplied buckets with different capacities and widths.

## Ground engaging tools

You can enhance the digging power and productivity of your excavator or wheel loader with Hitachi GET. Quick and safe to install and replace, they fit precisely to your attachments and can be tailored to suit the task. Using Hitachi GET can reduce your maintenance costs and downtime, lower fuel consumption and enhance the overall performance of your machine.

## Breakers

High-performance hydraulic breakers – approved by Hitachi – are perfectly suited to medium excavators. They are easy to maintain and user-friendly, and their high-quality materials ensure a long lifetime. This means reduced maintenance costs, fewer replacement parts and minimal downtime.



Attachments can be customised to suit the application.



Breakers are lightweight with high impact energy.



Hitachi GET include teeth and reliable adapters to ensure a precise fit.  
\*Not available in all markets



High performance hydraulic quick hitches approved by Hitachi.



# SPECIFICATIONS

ENGINE	
Model	TOYOTA INDUSTRIES CORPORATION 1KDE
Type	4-cycle water-cooled, common rail direct injection
Aspiration	Turbocharged, intercooled, cooled EGR
Aftertreatment	DOC and CSF system
No. of cylinders	4
Rated power	
ISO 14396 : 2002 gross	74 kW at 2 000 at min <sup>-1</sup>
ISO 9249 : 2007 net	73 kW at 2 000 at min <sup>-1</sup>
Maximum torque	390 Nm at 1 700 at min <sup>-1</sup>
Piston displacement	2.982 L
Bore and stroke	96 mm x 103 mm
Batteries	2 x 12 V / 74 Ah

HYDRAULIC SYSTEM			
Hydraulic Pumps			
Main pumps	2 variable displacement axial piston pumps		
Maximum oil flow	2 x 117 L/min		
Pilot pump	1 gear pump		
Maximum oil flow	33.6 L/min		
Hydraulic Motors			
Travel	2 variable displacement axial piston motors		
Swing	1 axial piston motor		
Relief Valve Settings			
Implement circuit	34.3 MPa		
Swing circuit	32.3 MPa		
Travel circuit	34.3 MPa		
Pilot circuit	3.9 MPa		
Power boost	36.3 MPa		
Hydraulic Cylinders			
	Quantity	Bore	Rod diameter
Boom	2	105 mm	70 mm
Arm	1	115 mm	80 mm
Bucket	1	100 mm	70 mm

UPPERSTRUCTURE	
Revolving Frame	
D-section frame for resistance to deformation.	
Swing Device	
Axial piston motor with planetary reduction gear is bathed in oil. Swing circle is single-row. Swing parking brake is spring-set/hydraulic-released disc type.	
Swing speed	13.3 min <sup>-1</sup>
Swing torque	34 kNm

UNDERCARRIAGE		
Tracks		
Tractor-type undercarriage. Welded track frame using selected materials. Side frame welded to track frame. Lubricated track rollers, idlers, and sprockets with floating seals. Track shoes with triple grousers made of induction-hardened rolled alloy. Heat-treated connecting pins with dirt seals. Hydraulic (grease) track adjusters with shock-absorbing recoil springs.		
Numbers of Rollers and Shoes on Each Side		
	ZX130-7	ZX130LCN-7
Upper rollers	1	2
Lower rollers		
	7	7
Track shoes		
	44	46
Track guards		
	1	2
Travel Device		
Each track driven by 2-speed axial piston motor. Parking brake is spring-set/hydraulic-released disc type. Automatic transmission system: High-Low.		
Travel speeds	High: 5.5 km/h	
	Low: 3.3 km/h	
Maximum traction force	117 kN	
Gradeability	70% (35 degree) continuous	

SERVICE REFILL CAPACITIES	
Fuel tank	285 L
Engine coolant	19 L
Engine oil	19.1 L
Swing device	3.2 L
Travel device (each side)	4.2 L
Hydraulic system	198 L
Hydraulic oil tank	82 L

ENVIRONMENT	
Engine Emissions	EU Stage V
Sounds Level	
Sound level in cab according to ISO 6396 : 2008	69 LpA dB(A)
External sound level according to ISO 6395 : 2008 and EU Directive 2000/14/EC	98 LwA dB(A)
Air Conditioning System	
The air conditioning system contains fluorinated greenhouse gases. Refrigerant type: HFC-134a, GWP: 1430, Amount: 0.85kg, CO2e: 1.22ton.	

# SPECIFICATIONS

## WEIGHTS AND GROUND PRESSURE

### Operating Weight and Ground Pressure


			ZAXIS 130 <sup>*1</sup>		ZAXIS 130 <sup>*1</sup> with blade (optional)		ZAXIS 130LCN <sup>*1</sup>	
Boom type			Monoblock		Monoblock		Monoblock	
Shoe type	Shoe width (mm)	Arm length (m)	kg	kPa	kg	kPa	kg	kPa
Triple grouser	500 mm	2.52 m	13 500	43	14 700	46	14 100	42
		3.01 m	13 600	43	14 800	46	14 200	42
	600 mm	2.52 m	13 800	36	15 000	39	14 400	36
		3.01 m	13 900	36	15 100	39	14 500	36
	700 mm	2.52 m	14 000	32	15 200	34	14 600	31
		3.01 m	14 100	32	15 300	34	14 700	31

\*1 Including 0.52 m<sup>3</sup> (ISO 7451:2007 heaped) bucket weight (410 kg) and counterweight (3 000 kg).

## BASIC MACHINE WEIGHT AND COMPONENTS WEIGHT

### Basic Machine Weight and Overall Width

Excluding front end attachment, fuel, hydraulic oil and coolant etc. Including counterweight (3 000 kg).



		ZX130-7		ZX130-7 with blade (optional)		ZX130LCN-7	
Shoe type	Shoe width (mm)	Weight (kg)	Overall width (mm)	Weight (kg)	Overall width (mm)	Weight (kg)	Overall width (mm)
Triple grouser	500	10 700	2 490	11 900	2 490 / 2 690*	11 000	2 490
	600	11 000	2 590	12 100	2 590 / 2 690*	11 300	2 590
	700	11 200	2 690	12 400	2 690	11 500	2 690

\* With optional wide blade

### Components Weight

Unit: kg

	ZX130-7	ZX130LCN-7
Counterweight	3 000 kg	3 000 kg
Monoblock boom (with arm cylinder and boom cylinder)	1 260 kg	1 260 kg
Arm 2.52 m (with bucket cylinder)	610 kg	610 kg
Arm 3.01 m (with bucket cylinder)	680 kg	680 kg
Bucket ISO7451:2007 0.52 m <sup>3</sup>	410 kg	410 kg

## BUCKET AND ARM DIGGING FORCE

Unit: kN


		ZX130-7		ZX130LCN-7	
Arm length		2.52 m	3.01 m	2.52 m	3.01 m
Bucket Digging Force at Power Boost ISO		104 kN	104 kN	104 kN	104 kN
Arm Crowd Force at Power Boost ISO		69 kN	61 kN	69 kN	61 kN



## WORKING RANGES

## MONOBLOCK BOOM

meter




Unit: mm

	ZX130-7		ZX130LCN-7	
	Monoblock boom			
Arm length	2.52 m	3.01 m	2.52 m	3.01 m
A Max. digging reach	8 300	8 770	8 300	8 770
A' Max. digging reach (on ground)	8 170	8 650	8 170	8 650
B Max. digging depth	5 540	6 030	5 540	6 030
B' Max. digging depth for 2.44 m level	5 310	5 840	5 310	5 840
C Max. cutting height	8 600	8 930	8 600	8 930
D Max. dumping height	6 190	6 520	6 190	6 520
D' Min. dumping height	2 070	1 610	2 070	1 610
E Min. swing radius	2 400	2 620	2 400	2 620
F Max. vertical wall digging depth	4 750	5 220	4 750	5 220

Excluding track shoe lug

# SPECIFICATIONS

## DIMENSIONS



Unit: mm

	ZX130-7	ZX130LCN-7
	Monoblock boom	
A Distance between tumblers	2 880	3 050
B Undercarriage length	3 580	3 750
*C Counterweight clearance	840	840
D Rear-end swing radius	2 190	2 190
D' Rear-end length	2 190	2 190
E Overall width of upperstructure	2 460	2 460
F Overall height of cab	2 870	2 790
F' Overall height of handrail	2 870	2 870
*G Min. ground clearance	410	410
H Track gauge	1 990	1 990
I Track shoe width	500	500
J Undercarriage width	2 490	2 490
K Overall width	2 490	2 490
*L Track height with triple grouser shoes	790	790
M Overall length		
With Arm 2.52 m	7 700	7 700
With Arm 3.01 m	7 710	7 710
N Overall height of boom		
With Arm 2.52 m	2 800	2 800
With Arm 3.01 m	2 680	2 680
O Blade Height	600	600
P Blade Width	2 490 / 2 690 (optional)	-
Q Distance Between The Front End Of Blade And The Axis Of Rotation	2 540	-
R Blade Maximum Lifting	480	-
S Blade Maximum Lowering	530	-
T Blade Approach Angle	23 °	-


\*1 Excluding track shoe lug

\*2 The dimensions asterisked are for transport pin position.

G: Triple grouser shoe

# MACHINE CAPACITIES

- Notes:
1. Ratings are based on ISO 10567 : 2007.
  2. Machine capacity does not exceed 75% of tipping load with the machine on firm, level ground or 87% full hydraulic capacity.
  3. The load point is the center-line of the bucket pivot mounting pin on the arm.
  4. \*Indicates load limited by hydraulic capacity.
  5. 0 m = Ground.



- A: Load radius  
B: Load point height  
C: Machine capacity













For machine capacities, subtract installed attachment and quick hitch weight from machine capacities.

To determine lifting capacities, apply "Rating over-side or 360 degrees" machine capacities from the table and deduct weight of installed attachment and quick hitch.

Optional feature may affect machine performance.













## ZX130-7 MONOBLOCK BOOM

Rating over-front Rating over-side or 360 degrees Unit : kg

Conditions	Load point height m	Load radius										At max. reach		
		1.5 m		3.0 m		4.5 m		6.0 m		7.5 m				
														meter
Boom 4.80 m Arm 2.52 m Counterweight 3 000 kg	4.5					*3 550	*3 550	*3 330	2 590			*2 280	*2 280	6.36
	3.0			*5 880	*5 880	*4 330	3 900	3 590	2 520			*2 280	2 020	6.90
	1.5			*8 060	6 590	*5 310	3 660	3 480	2 420			*2 400	1 900	7.07
	0 (Ground)			*6 480	6 270	5 190	3 480	3 390	2 340			*2 690	1 920	6.92
	-1.5	*4 630	*4 630	*9 090	6 230	5 110	3 410	3 360	2 310			3 070	2 120	6.40
	-3.0	*8 520	*8 520	*7 780	6 330	5 150	3 450					3 920	2 690	5.44
Boom 4.60 m Arm 3.01 m Counterweight 3 000 kg	6.0											*2 110	*2 110	5.97
	4.5					*3 070	*3 070	*3 120	2 620			*1 970	*1 970	6.88
	3.0			*4 880	*4 880	*3 880	*3 880	*3 430	2 540			*1 960	1 810	7.38
	1.5			*7 660	6 740	*4 930	3 690	3 490	2 420	*2 220	1 720	*2 050	1710	7.54
	0 (Ground)			*7 090	6 270	5 180	3 470	3 370	2 320			*2 270	1 720	7.39
	-1.5	*4 080	*4 080	*8 880	6 150	5 060	3 360	3 310	2 260			*2 690	1 870	6.92
	-3.0	*7 140	*7 140	*8 330	6 200	5 060	3 360	3 340	2 290			3 320	2 270	6.04
	-4.5			*6 020	*6 020	*3 700	3 520					*3 690	3 520	4.50

## ZX130-7 WITH BLADE MONOBLOCK BOOM



Rating over-front Rating over-side or 360 degrees Unit : kg













Conditions	Load point height m	Load radius										At max. reach		
		1.5 m		3.0 m		4.5 m		6.0 m		7.5 m				
														meter
Boom 4.80 m Arm 2.52 m Counterweight 3 000 kg	4.5					*3 550	*3 550	*3 330	2 780			*2 280	*2 280	6.36
	3.0			*5 880	*5 880	*4 330	4 180	3 570	2 720			*2 280	2 180	6.90
	1.5			*8 060	7 090	*5 310	3 930	3 460	2 620			*2 400	2 060	7.07
	0 (Ground)			*6 480	*6 480	5 150	3 760	3 370	2 530			*2 690	2 090	6.92
	-1.5	*4 630	*4 630	*9 090	6 730	5 080	3 690	3 340	2 500			3 050	2 300	6.40
	-3.0	*8 520	*8 520	*7 780	6 830	5 120	3 730					3 890	2 900	5.44
Boom 4.60 m Arm 3.01 m Counterweight 3 000 kg	6.0											*2 110	*2 110	5.97
	4.5					*3 070	*3 070	*3 120	2 820			*1 970	*1 970	6.88
	3.0			*4 880	*4 880	*3 880	*3 880	*3 430	2 730			*1 960	*1 960	7.38
	1.5			*7 660	7 240	*4 930	3 960	3 460	2 620	*2 220	1 870	*2 050	1 850	7.54
	0 (Ground)			*7 090	6 760	5 150	3 750	3 350	2 510			*2 270	1 870	7.39
	-1.5	*4 080	*4 080	*8 880	6 640	5 030	3 640	3 290	2 460			*2 690	2 030	6.92
	-3.0	*7 140	*7 140	*8 330	6 690	5 030	3 640	3 320	2 480			3 300	2 470	6.04
	-4.5			*6 020	*6 020	*3 700	*3 700					*3 690	*3 690	4.50



# SPECIFICATIONS

## ZX130LCN-7 MONOBLOCK BOOM

 Rating over-front  Rating over-side or 360 degrees Unit : kg

Conditions	Load point height m	Load radius										At max. reach		
		1.5 m		3.0 m		4.5 m		6.0 m		7.5 m				
														meter
Boom 4.60 m Arm 2.52 m Counterweight 3 000 kg	4.5					*3 520	*3 540	*3 320	2 670			*2 270	*2 270	6.36
	3.0			*5 860	*5 860	*4 320	4 030	*3 720	2 610			*2 260	2 090	6.90
	1.5			*8 050	6 820	*5 300	3 780	3 880	2 510			*2 390	1 960	7.07
	0 (Ground)			*6 470	*6 470	5 830	3 600	3 790	2 420			*2 680	1 990	6.92
	-1.5	*4 620	*4 620	*9 070	6 460	5 750	3 530	3 750	2 390			*3 270	2 200	6.40
	-3.0	*8 510	*8 510	*7 770	6 560	*5 270	3 570					*4 010	2 780	5.44
Boom 4.60 m Arm 3.01 m Counterweight 3 000 kg	6.0											*2 090	*2 090	5.97
	4.5					*3 060	*3 060	*3 100	2 710			*1 950	*1 950	6.88
	3.0			*4 860	*4 860	*3 860	*3 860	*3 420	2 620			*1 950	1 870	7.38
	1.5			*7 650	6 970	*4 910	3 810	*3 880	2 510	*2 210	1 780	*2 040	1 770	7.54
	0 (Ground)			*7 080	6 500	*5 730	3 590	3 770	2 400			*2 260	1 780	7.39
	-1.5	*4 070	*4 070	*8 870	6 380	5 710	3 490	3 700	2 350			*2 680	1 940	6.92
	-3.0	*7 130	*7 130	*8 310	6 430	*5 560	3 490	3 740	2 370			*3 600	2 360	6.04
	-4.5			*6 000	*6 000	*3 680	3 650					*3 680	3 640	4.50

● : Standard equipment ○ : Optional equipment – : Not applicable

ENGINE	ZX130-7 / ZX130LCN-7	
Aftertreatment device	●	●
Air cleaner double filters	●	●
Alternator 60 A	●	●
Auto idle system	●	●
Auto shut-down control	●	●
Cartridge-type engine oil filter	●	●
Cartridge-type fuel main filter	●	●
ConSite OIL (sensor)*	●	●
Dry-type air filter with evacuator valve (with air filter restriction indicator)	●	●
Dust-proof indoor net	●	●
ECO/PWR mode control	●	●
Electrical fuel feed pump	●	●
Engine oil drain coupler	●	●
Expansion tank	●	●
Fan guard	●	●
Fuel cooler	●	●
Fuel pre-filter with water separator	●	●
Isolation-mounted engine	●	●
Maintenance free pre-cleaner	●	●
Oil separator	●	●
Radiator, oil cooler and intercooler	●	●
Belt auto tensioner	●	●

HYDRAULIC SYSTEM	ZX130-7 / ZX130LCN-7	
Auto power lift	●	●
Control valve with main relief valve	●	●
Extra port for control valve	●	●
Full flow filter	●	●
High mesh full flow filter with restriction indicator	○	○
Hose rupture valve for arm	●	●
Hose rupture valve for boom	●	●
Pilot filter	●	●
Power boost	●	●
Suction filter	●	●
Variable reliefvalve for breaker and crusher	●	●
Work mode selector	●	●
ConSite OIL (sensor)*	●	●

\* Engine oil and hydraulic oil monitoring sensor.

CAB	ZX130-7 / ZX130LCN-7	
All-weather sound suppressed steel cab	●	●
Bluetooth® integrated DAB+radio	●	●
Hands-free calling device	●	●
Auto control air conditioner	●	●
AUX function lever (breaker assist)	○	○
Wide view wiper	○	○
Console height adjustment	●	●
CRES VII (center pillar reinforced structure) cab	●	●
Drink holder with hot and cool function	●	●
Electric double horn	●	●
Engine shut-off switch	●	●
Equipped with reinforced, tinted (green color) glass windows	●	●
Evacuation hammer	●	●
Floor mat	●	●
Footrest	●	●
Front window washer (1 points)	●	●
Front window washer (2 points)	○	○
Glove compartment	●	●
Hot and cool box	●	●
Intermittent windshield wipers	●	●
Key cylinder light	●	●
Laminated round glass window	●	●
LED room light	●	●
Magazine rack	●	●
OPG front guard Level II ISO 10262 : 1998) compliant	○	○
OPG top guard Level II ISO 10262 : 1998) compliant	●	●
Pilot shut-off lever	●	●
Power outlet 12 V and 24V	●	●
Rain guard (without OPG front guard)	○	○
Rear tray	●	●
Retractable seat belt	●	●
ROPS(ISO 12117-2 : 2008) compliant cab	●	●
Rubber radio antenna	●	●
Seat : air suspension seat with heater	●	●
Seat adjustment part : backrest, armrest, height and angle, slide forward / back	●	●
Seat belt reminder	●	●
Short wrist control levers	●	●
Sunscreen roller type (multi-use front or side and rear window)	●	●
Smartphone holder	●	●
Transparent roof with slide curtain	●	●
USB power supply	●	●
Windows on front, upper, lower and left side can be opened	●	●
2 speakers	●	●
4 fluid-filled elastic mounts	●	●
8 inch monitor	●	●
Push button low idle	●	●
Control lever auto-lock	●	●

MONITOR SYSTEM	ZX130-7 / ZX130LCN-7	
Alarms: overheat, engine warning, engine oil pressure, alternator, minimum fuel level, hydraulic filter restriction, air filter restriction, work mode, overload, etc	●	●
Alarm buzzers: overheat, engine oil pressure, overload, etc	●	●
Display of meters: water temperature, hour, fuel rate, clock, etc	●	●
Other displays: work mode, auto-idle, glow, rearview monitor, operating conditions, etc	●	●
35 languages selection	●	●

LIGHTS	ZX130-7 / ZX130LCN-7	
Additional boom LED light with cover	○	○
Additional cab roof front LED lights	○	○
Additional cab roof rear LED lights	●	●
LED lights for camera (side and rear view camera)	●	●
2 working LED lights	●	●

UPPER STRUCTURE	ZX130-7 / ZX130LCN-7	
Aerial Angle® (270-degree view camera system)	●	●
Batteries 2 x 74 Ah	●	●
Battery disconnect switch	●	●
Cab top handhold	●	●
Body top handrail	●	●
Counterweight 3 000 kg	●	●
Fuel level float	●	●
Hydraulic oil level gauge	●	●
Lockable fuel refilling cap	●	●
Lockable machine covers	●	●
Lockable tool box	●	●
Platform handrail	●	●
Side view mirror (right and left)	●	●
Skid-resistant plates	●	●
Swing parking brake	●	●
Undercover	●	●
Undercover 6.0 mm reinforced	○	○

● : Standard equipment    ○ : Optional equipment    – : Not applicable

UNDERCARRIAGE	ZX130-7 / ZX130LCN-7	
Bolt-on sprocket	●	●
Blade 2 490 mm	○	–
Blade 2 690 mm	○	–
Reinforced track links with pin seals	●	●
Shoe: 500 mm triple grouser	●	–
Shoe: 600 mm triple grouser	○	●
Shoe: 700 mm triple grouser	○	○
Track undercover	●	●
Travel direction mark on track frame	●	●
Travel motor covers	●	●
Travel parking brake	●	●
Upper and lower rollers	●	●
1 track guard (each side)	●	○
2 track guards (each side)	○	●
4 tie down brackets	●	●
Towing hole for light weight object	●	●
Greasing type track adjuster	●	●

ATTACHMENTS	ZX130-7 / ZX130LCN-7	
Accessories for 2 speed selector	○	○
Additional pump or PTO valve	○	○
Assist piping	●	●
Breaker and crusher piping	●	●
Pilot accumulator	●	●

MISCELLANEOUS	ZX130-7 / ZX130LCN-7	
ConSite	●	●
Global e-service	●	●
Onboard information controller	●	●
Standard tool kit	●	●
Travel alarm	●	●
Satellite communication system unit	●	●
Level indicator	●	●

FRONT ATTACHMENTS	ZX130-7 / ZX130LCN-7	
Casted bucket link A	●	●
Centralized lubrication system	●	●
Dirt seal on all bucket pins	●	●
Flanged pin	●	●
HN bushing	●	●
Reinforced resin thrust plate	●	●
WC (tungsten-carbide) thermal spraying	●	●
Reinforced bucket link B	●	●
Arm tip remote lubrication	●	●
Lower arm reinforcement	●	●

Standard and optional equipment may vary by country, so please consult your Hitachi dealer for details.

Prior to operating this machine, including satellite communication system, in a country other than a country of its intended use, it may be necessary to make modifications to it so that it complies with the local regulatory standards (including safety standards) and legal requirements of that particular country. Please do not export or operate this machine outside the country of its intended use until such compliance has been confirmed. Please contact your Hitachi dealer in case of questions about compliance.

These specifications are subject to change without notice.

Illustrations and photos show the standard models, and may or may not include optional equipment, accessories, and all standard equipment with some differences in color and features. Before use, read and understand the Operator's Manual for proper operation.